



PIN CONNECTION

NO	SYMBOL	NO	SYMBOL
1	CS1B	15	VSS
2	RESET1B	16	VOUT
3	RS	17	C4+
4	RW_RWB	18	C3+
5	E_RDB	19	C1-
6	DB0	20	C1+
7	DB1	21	C2+
8	DB2	22	C2-
9	DB3	23	V1
10	DB4	24	V2
11	DB5	25	V3
12	DB6	26	V4
13	DB7	27	V0
14	VDD	28	PS

COM15	COM63
COM0	COM48
SEGO	SEG121

- NOTE:**
1. VIEWING ANGLE: 6:00 O' CLOCK
 2. DISPLAY MODE: POSITIVE, TRANSPARENT, YELLOW-GREEN, STN TYPE
 3. DRIVING VOLTAGE: 9.5V, DUTY: 1/33, BIAS: 1/6, FREQUENCY: 64Hz
 4. SUPPLY VOLTAGE: +3.3V
 5. OPERATING TEMP.: -15° C TO 70° C
 6. STORAGE TEMP.: -20° C TO 75° C
 7. CONNECTOR: FPC TYPE

TOLERANCES UNLESS OTHERWISE STATED
 XXX.X ±0.20 XX.X ±0.10 UNIT: mm

REVISION RECORD				XIAMEN OCULAR OPTICS CO.,LTD		
VER	Date	Modify Contents	Name	Confirm	Drawn:	Model Name:
2					ALAN	GDC12232B
3					Checker:	Date:
4					Approved:	2006.11.28
5					Page: 1-1	
6						

